



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing		
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs	
RDD1555B2-5	Ball	D	24	12	1.7	4500	320	9.061	31.29	62.26	•	•		•	•	725	20	15.5	
RDH1555B2-5				12	1.2	4000	281	7.957	27.73	60.41	•	•		•	•				
RDM1555B2-5				12	1.0	3800	268	7.589	26.39	59.44	•	•		•	•				
RDL1555B2-5				12	0.7	3400	236	6.683	20.99	55.71	•	•		•	•				
RDX1555B2-5				12	0.55	3100	223	6.315	18.26	53.25	•	•		•	•				
RDD1555B4-5	Ball		48	24	24	0.9	4500	320	9.061	31.29	62.26	•	•		•				•
RDH1555B4-5					24	0.65	4000	281	7.957	27.73	60.41	•	•		•				•
RDM1555B4-5					24	0.55	3800	268	7.589	26.39	59.44	•	•		•				•
RDL1555B4-5					24	0.45	3400	236	6.683	20.99	55.71	•	•		•				•
RDX1555B4-5					24	0.35	3100	223	6.315	18.26	53.25	•	•		•				•

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA
24V					
48V					

