



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing			
			VDC	VDC	A	RPM	CFM	CMM	mmH <sub>2</sub> O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs		
RDD1725B2-3	Ball	B	24	12	1.7	4600	336	9.515	31.22	63.11	•	•		•	•	775	20	16.7		
RDH1725B2-3				12	1.2	4200	305	8.637	25.79	60.74	•	•		•	•					
RDM1725B2-3				12	1.0	3900	280	7.929	23.16	58.28	•	•		•	•					
RDL1725B2-3				12	0.7	3500	253	7.164	18.66	56.85	•	•		•	•					
RDX1725B2-3				12	0.55	3200	236	6.683	14.57	54.35	•	•		•	•					
RDD1725B4-3	Ball		48	24	0.9	4600	336	9.515	31.22	63.11	63.11	•	•		•				•	
RDH1725B4-3					0.65	4200	305	8.637	25.79	60.74	60.74	60.74	•	•					•	•
RDM1725B4-3					0.55	3900	280	7.929	23.16	58.28	58.28	58.28	•	•					•	•
RDL1725B4-3					0.45	3500	253	7.164	18.66	56.85	56.85	56.85	•	•					•	•
RDX1725B4-3					0.35	3200	236	6.683	14.57	54.35	54.35	54.35	•	•					•	•

SAFETY APPROVALS ( 安規認證 )

	CE	UL	CUL	TUV	CSA
24V					
48V					

