



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing		
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs	
RDD1751B2-3	Ball	H	24	12	1.7	4600	336	9.515	31.22	63.11	•	•		•	•	725	20	15.6	
RDH1751B2-3				12	1.2	4200	305	8.637	25.79	60.74	•	•		•	•				
RDM1751B2-3				12	1.0	3900	280	7.929	23.16	58.28	•	•		•	•				
RDL1751B2-3				12	0.7	3500	253	7.164	18.66	56.85	•	•		•	•				
RDX1751B2-3				12	0.55	3200	236	6.683	14.57	54.35	•	•		•	•				
RDD1751B4-3	Ball		48	24	0.9	4600	336	9.515	31.22	63.11	63.11	•	•		•				•
RDH1751B4-3				24	0.65	4200	305	8.637	25.79	60.74	60.74	•	•		•				•
RDM1751B4-3				24	0.55	3900	280	7.929	23.16	58.28	58.28	•	•		•				•
RDL1751B4-3				24	0.45	3500	253	7.164	18.66	56.85	56.85	•	•		•				•
RDX1751B4-3				24	0.35	3200	236	6.683	14.57	54.35	54.35	•	•		•				•

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA
24V					
48V					

