



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH2510S5	Sleeve	N	5	3.5	0.16	13000	2.67	0.076	4.28	27.95	•	•			•	7	600	5.0
RDM2510S5				3.5	0.12	10000	2.06	0.058	3.63	23.18	•	•			•			
RDL2510S5				3.5	0.08	8000	1.65	0.047	2.03	20.36	•	•			•			
RDH2510B5	Ball			3.5	0.16	13000	2.67	0.076	4.28	27.95	•	•			•			
RDM2510B5				3.5	0.12	10000	2.06	0.058	3.63	23.18	•	•			•			
RDL2510B5				3.5	0.08	8000	1.65	0.047	2.03	20.36	•	•			•			
RDH2510S	Sleeve	N	12	6.0	0.10	13000	2.67	0.076	4.28	27.95	•	•			•	7	600	5.0
RDM2510S				6.0	0.08	10000	2.06	0.058	3.63	23.18	•	•			•			
RDL2510S				6.0	0.06	8000	1.65	0.047	2.03	20.36	•	•			•			
RDH2510B	Ball			6.0	0.10	13000	2.67	0.076	4.28	27.95	•	•			•			
RDM2510B				6.0	0.08	10000	2.06	0.058	3.63	23.18	•	•			•			
RDL2510B				6.0	0.06	8000	1.65	0.047	2.03	20.36	•	•			•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
5V	•	•	•	•
12V	•	•	•	•

