



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBa	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH4010S5	Sleeve	N	5	3.5	0.20	7000	7.67	0.217	3.77	30.30	•	•		•	•	16	600	11.8
RDM4010S5				3.5	0.16	6000	6.45	0.182	2.83	26.57	•	•		•	•			
RDL4010S5				3.5	0.13	5000	5.29	0.149	2.04	22.69	•	•		•	•			
RDH4010B5	Ball			3.5	0.20	7000	7.67	0.217	3.77	30.30	•	•		•	•			
RDM4010B5				3.5	0.16	6000	6.45	0.182	2.83	26.57	•	•		•	•			
RDL4010B5				3.5	0.13	5000	5.29	0.149	2.04	22.69	•	•		•	•			
RDH4010S	Sleeve	12	6.0	0.09	7000	7.67	0.217	3.77	30.30	•	•		•	•				
RDM4010S			6.0	0.07	6000	6.45	0.182	2.83	26.57	•	•		•	•				
RDL4010S			7.0	0.06	5000	5.29	0.149	2.04	22.69	•	•		•	•				
RDH4010B	Ball		6.0	0.07	7000	7.67	0.217	3.77	30.30	•	•		•	•				
RDM4010B			6.0	0.06	6000	6.45	0.182	2.83	26.57	•	•		•	•				
RDL4010B			7.0	0.05	5000	5.29	0.149	2.04	22.69	•	•		•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA
5V	•	•	•	•	
12V	•	•	•	•	•

