



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH <sub>2</sub> O	dBa	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH4020S5	Sleeve	N	5	3.5	0.40	8000	9.11	0.258	6.90	31.40	•	•	•	•	•	29	400	13.1
RDH4020S5				3.5	0.28	7500	8.59	0.243	6.18	29.62	•	•	•	•	•			
RDM4020S5				3.5	0.25	6200	6.99	0.197	4.29	25.15	•	•	•	•	•			
RDL4020S5				3.5	0.20	5000	5.53	0.156	2.74	21.23	•	•	•	•	•			
RDH4020B5	Ball			3.5	0.40	8000	9.11	0.258	6.90	31.40	•	•	•	•	•			
RDH4020B5				3.5	0.28	7500	8.59	0.243	6.18	29.62	•	•	•	•	•			
RDM4020B5				3.5	0.25	6200	6.99	0.197	4.29	25.15	•	•	•	•	•			
RDL4020B5				3.5	0.20	5000	5.53	0.156	2.74	21.23	•	•	•	•	•			
RDH4020S	Sleeve	12	6.0	0.12	8000	9.11	0.258	6.90	31.40	•	•	•	•	•				
RDH4020S			6.0	0.12	7500	8.59	0.243	6.18	29.62	•	•	•	•	•				
RDM4020S			6.0	0.10	6200	6.99	0.197	4.29	25.15	•	•	•	•	•				
RDL4020S			6.0	0.06	5000	5.53	0.156	2.74	21.23	•	•	•	•	•				
RDH4020B	Ball		6.0	0.12	8000	9.11	0.258	6.90	31.40	•	•	•	•	•				
RDH4020B			6.0	0.12	7500	8.59	0.243	6.18	29.62	•	•	•	•	•				
RDM4020B			6.0	0.10	6200	6.99	0.197	4.29	25.15	•	•	•	•	•				
RDL4020B			6.0	0.06	5000	5.53	0.156	2.74	21.23	•	•	•	•	•				
RDH4020S2	Sleeve	24	12.0	0.07	8000	9.11	0.258	6.90	31.40	•	•	•	•	•				
RDH4020S2			12.0	0.06	7500	8.59	0.243	6.18	29.62	•	•	•	•	•				
RDM4020S2			12.0	0.05	6200	6.99	0.197	4.29	25.15	•	•	•	•	•				
RDL4020S2			12.0	0.04	5000	5.53	0.156	2.74	21.23	•	•	•	•	•				
RDH4020B2	Ball		12.0	0.07	8000	9.11	0.258	6.90	31.40	•	•	•	•	•				
RDH4020B2			12.0	0.06	7500	8.59	0.243	6.18	29.62	•	•	•	•	•				
RDM4020B2			12.0	0.05	6200	6.99	0.197	4.29	25.15	•	•	•	•	•				
RDL4020B2			12.0	0.04	5000	5.53	0.156	2.74	21.23	•	•	•	•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA
5V	•	•	•	•	
12V	•	•	•	•	•
24V					

