



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBa	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH5010S5	Sleeve	H	5	3.5	0.30	5300	13.27	0.375	3.38	28.16	•	•		•	•	19	600	12.9
RDM5010S5				3.5	0.20	4500	11.02	0.312	2.53	24.06	•	•		•	•			
RDL5010S5				3.5	0.14	3500	8.69	0.246	1.67	20.32	•	•		•	•			
RDH5010B5	Ball			3.5	0.30	5300	7.76	0.217	3.77	30.30	•	•		•	•			
RDM5010B5				3.5	0.20	4500	6.45	0.182	2.83	26.57	•	•		•	•			
RDL5010B5				3.5	0.14	3500	5.29	0.149	2.04	22.69	•	•		•	•			
RDH5010S	Sleeve	H	12	6.0	0.16	5300	13.27	0.375	3.38	28.16	•	•		•	•	19	600	12.9
RDM5010S				6.0	0.08	4500	11.02	0.312	2.53	24.06	•	•		•	•			
RDL5010S				7.0	0.07	3500	8.69	0.246	1.67	20.32	•	•		•	•			
RDH5010B	Ball			6.0	0.13	5300	7.67	0.217	3.77	30.30	•	•		•	•			
RDM5010B				6.0	0.07	4500	6.45	0.182	2.83	26.57	•	•		•	•			
RDL5010B				7.0	0.06	3500	5.29	0.149	2.04	22.69	•	•		•	•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA
5V	•	•	•	•	
12V	•	•	•	•	•

