



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH <sub>2</sub> O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH6020S	Sleeve	B	12	6.0	0.16	4000	16.08	0.455	3.92	26.88	•	•	•	•	•	50	200	11.5
RDM6020S				6.0	0.12	3300	13.28	0.376	2.74	23.30	•	•	•	•	•			
RDL6020S				6.0	0.08	2500	9.99	0.282	1.61	20.65	•	•	•	•	•			
RDH6020B	Ball			6.0	0.16	4000	16.08	0.455	3.92	26.88	•	•	•	•	•			
RDM6020B				6.0	0.12	3300	13.28	0.376	2.74	23.30	•	•	•	•	•			
RDL6020B				6.0	0.08	2500	9.99	0.282	1.61	20.65	•	•	•	•	•			
RDH6020S2	Sleeve	24	12.0	0.13	4000	16.08	0.455	3.92	26.88	•	•	•	•	•				
RDM6020S2			12.0	0.10	3300	13.28	0.376	2.74	23.30	•	•	•	•	•				
RDL6020S2			12.0	0.08	2500	9.99	0.282	1.61	20.65	•	•	•	•	•				
RDH6020B2	Ball		12.0	0.13	4000	16.08	0.455	3.92	26.88	•	•	•	•	•				
RDM6020B2			12.0	0.10	3300	13.28	0.376	2.74	23.30	•	•	•	•	•				
RDL6020B2			12.0	0.08	2500	9.99	0.282	1.61	20.65	•	•	•	•	•				

### SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA	VDE
12V	•	•	•	•	•	
24V						•

