



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH7025S5	Sleeve	H	5	3.5	0.70	4500	34.63	0.980	5.70	35.96	•	•	•	•	•	65	100	7.6
RDM7025S5				3.5	0.55	4000	31.53	0.893	4.95	31.49	•	•	•	•	•			
RDL7025S5				3.5	0.30	3000	23.72	0.672	3.10	24.84	•	•	•	•	•			
RDH7025B5	Ball			3.5	0.70	4500	34.63	1.151	5.70	35.96	•	•	•	•	•			
RDM7025B5				3.5	0.55	4000	31.53	0.893	4.95	31.49	•	•	•	•	•			
RDL7025B5				3.5	0.30	3000	23.72	0.672	3.10	24.84	•	•	•	•	•			
RDH7025S	Sleeve	12	6.0	0.40	5100	40.64	1.151	7.57	37.84	•	•	•	•	•				
RDM7025S			6.0	0.20	4000	31.53	0.893	4.95	31.49	•	•	•	•	•				
RDL7025S			6.0	0.15	3000	23.72	0.672	3.10	24.84	•	•	•	•	•				
RDH7025B	Ball		6.0	0.40	5100	40.64	1.151	7.57	37.84	•	•	•	•	•				
RDM7025B			6.0	0.20	4000	31.53	0.893	4.95	31.49	•	•	•	•	•				
RDL7025B			6.0	0.15	3000	23.72	0.672	3.10	24.84	•	•	•	•	•				
RDH7025S2	Sleeve	24	12.0	0.22	5100	40.64	1.151	7.57	37.84	•	•	•	•	•				
RDM7025S2			12.0	0.12	4000	31.53	0.893	4.95	31.49	•	•	•	•	•				
RDL7025S2			12.0	0.10	3000	23.72	0.672	3.10	24.84	•	•	•	•	•				
RDH7025B2	Ball		12.0	0.20	5100	40.64	1.151	7.57	37.84	•	•	•	•	•				
RDM7025B2			12.0	0.12	4000	31.53	0.893	4.95	31.49	•	•	•	•	•				
RDL7025B2			12.0	0.10	3000	23.72	0.672	3.10	24.84	•	•	•	•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
5V	•	•	•	•
12V	•	•	•	•
24V	•	•	•	•

