



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH8015S	Sleeve	B	12	6.0	0.17	3000	31.22	0.8841	2.66	31.06	•	•	•	•	•	40	200	10.0
RDM8015S				6.0	0.14	2500	26.01	0.7365	1.95	27.08	•	•	•	•	•			
RDL8015S				6.0	0.09	2000	20.87	0.591	1.28	22.08	•	•	•	•	•			
RDH8015B	Ball			6.0	0.17	3000	31.22	0.8841	2.66	31.06	•	•	•	•	•			
RDM8015B				6.0	0.14	2500	26.01	0.7365	1.95	27.08	•	•	•	•	•			
RDL8015B				6.0	0.09	2000	20.87	0.591	1.28	22.08	•	•	•	•	•			
RDH8015S2	Sleeve	24	12.0	0.15	3000	31.22	0.8841	2.66	31.06	•	•	•	•	•				
RDM8015S2			12.0	0.13	2500	26.01	0.7365	1.95	27.08	•	•	•	•	•				
RDL8015S2			12.0	0.10	2000	20.87	0.591	1.28	22.08	•	•	•	•	•				
RDH8015B2	Ball		12.0	0.15	3000	31.22	0.8841	2.66	31.06	•	•	•	•	•				
RDM8015B2			12.0	0.13	2500	26.01	0.7365	1.95	27.08	•	•	•	•	•				
RDL8015B2			12.0	0.10	2000	20.87	0.591	1.28	22.08	•	•	•	•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA	VDE
12V	•	•	•	•	•	
24V						•

