



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH8020S	Sleeve	E	12	6.0	0.23	3500	38.81	1.099	3.30	35.49	•	•	•	•	•	64	100	7.3
RDM8020S				6.0	0.17	3000	33.50	0.9486	2.49	31.73	•	•	•	•	•			
RDL8020S				6.0	0.13	2500	27.69	0.7841	1.77	26.82	•	•	•	•	•			
RDH8020B	Ball			6.0	0.23	3500	38.81	1.099	3.30	35.49	•	•	•	•	•			
RDM8020B				6.0	0.17	3000	33.50	0.9486	2.49	31.73	•	•	•	•	•			
RDL8020B				6.0	0.13	2500	27.69	0.7481	1.77	26.82	•	•	•	•	•			
RDH8020S2	Sleeve	E	24	12.0	0.21	3500	38.81	1.099	3.30	35.49	•	•	•	•	•	64	100	7.3
RDM8020S2				12.0	0.14	3000	33.50	0.9486	2.49	31.73	•	•	•	•	•			
RDL8020S2				12.0	0.12	2500	27.69	0.7841	1.77	26.82	•	•	•	•	•			
RDH8020B2	Ball			12.0	0.21	3500	38.81	1.099	3.30	35.49	•	•	•	•	•			
RDM8020B2				12.0	0.14	3000	33.50	0.9486	2.49	31.73	•	•	•	•	•			
RDL8020B2				12.0	0.12	2500	27.69	0.7481	1.77	26.82	•	•	•	•	•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
12V	•	•	•	•
24V	•	•	•	•

