



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBA	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RDH8025S1	Sleeve	H	12	6.0	0.23	3000	41.00	1.161	3.32	29.77	•	•	•	•	•	76	100	9.0
RDM8025S1				6.0	0.16	2500	33.42	0.946	2.29	25.10	•	•	•	•	•			
RDL8025S1				6.0	0.13	2000	26.57	0.752	1.54	21.21	•	•	•	•	•			
RDH8025B1	Ball			6.0	0.23	3000	41.00	1.161	3.32	29.77	•	•	•	•	•			
RDM8025B1				6.0	0.16	2500	33.42	0.946	2.29	25.10	•	•	•	•	•			
RDL8025B1				6.0	0.13	2000	26.57	0.752	1.54	21.21	•	•	•	•	•			
RDH8025S2	Sleeve	24	12.0	0.15	0.12	3000	41.00	1.161	3.32	29.77	•	•	•	•	•			
RDM8025S2				0.12	2500	33.42	0.946	2.29	25.10	•	•	•	•	•	•			
RDL8025S2				0.09	2000	26.57	0.752	1.54	21.21	•	•	•	•	•	•			
RDH8025B2	Ball			0.15	0.12	3000	41.00	1.161	3.32	29.77	•	•	•	•	•	•		
RDM8025B2				0.12	2500	33.42	0.946	2.29	25.10	•	•	•	•	•	•			
RDL8025B2				0.09	2000	26.57	0.752	1.54	21.21	•	•	•	•	•	•			

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV	CSA	VDE
12V	•	•	•	•	•	
24V	•	•	•	•		•

