



Listed Model	Bearing System	Housing Type	Rated Voltage	Startup Voltage	Rated Current	Speed	Air Flow	Air Flow	Static Pressure	Noise Level	Motor Protection					Weight Gram	Packing	
			VDC	VDC	A	RPM	CFM	CMM	mmH ₂ O	dBa	Resistance Protected	Auto Start	Thermal Speed Control	Alarm Output	Tachometer Output		Qty./Ctn Purchase	G.W./Ctn Kgs
RBH9733S	Sleeve	A	12	6.0	0.80	3300	21.80	0.617	20.42	45.47	•	•	•	•	•	165	80	15.0
RBM9733S				6.0	0.50	2800	18.44	0.522	13.59	41.51	•	•	•	•	•			
RBL9733S				6.0	0.30	2200	14.43	0.408	7.74	35.30	•	•	•	•	•			
RBH9733B	Ball			6.0	0.80	3300	21.80	0.617	20.42	45.47	•	•	•	•	•			
RBM9733B				6.0	0.50	2800	18.44	0.522	13.59	41.51	•	•	•	•	•			
RBL9733B				6.0	0.30	2200	14.43	0.408	7.74	35.30	•	•	•	•	•			
RBH9733S2	Sleeve	24	12.0	0.55	3300	21.80	0.617	20.42	45.47	•	•	•	•	•				
RBM9733S2			12.0	0.35	2800	18.44	0.522	13.59	41.51	•	•	•	•	•				
RBL9733S2			12.0	0.20	2200	14.43	0.408	7.74	35.30	•	•	•	•	•				
RBH9733B2	Ball		12.0	0.55	3300	21.80	0.617	20.42	45.47	•	•	•	•	•				
RBM9733B2			12.0	0.35	2800	18.44	0.522	13.59	41.51	•	•	•	•	•				
RBL9733B2			12.0	0.20	2200	14.43	0.408	7.74	35.30	•	•	•	•	•				
RBH9733S4	Sleeve	48	24.0	0.30	3300	21.80	0.617	20.42	45.47	•	•	•	•	•				
RBM9733S4				0.20	2800	18.44	0.522	13.59	41.51	•	•	•	•	•				
RBL9733S4				0.15	2200	14.43	0.408	7.74	35.30	•	•	•	•	•				
RBH9733B4	Ball			0.30	3300	21.80	0.617	20.42	45.47	•	•	•	•	•				
RBM9733B4				0.20	2800	18.44	0.522	13.59	41.51	•	•	•	•	•				
RBL9733B4				0.15	2200	14.43	0.408	7.74	35.30	•	•	•	•	•				

SAFETY APPROVALS (安規認證)

	CE	UL	CUL	TUV
12V	•	•	•	•
24V	•	•	•	•
48V	•	•	•	•

